
Voltron® Lighting Group

Technical product sheet


Elegance track light






ELEG-25W-2700K-BL-BL-36

VOLTRON® ELEGANCE 3-phase TRACK light is high subtlety and quality in one design. The luminaire is built according to the circular principle: fast replacement of power supply and light source. Available in 3 powers namely 10W, 25W or 35W and 2 beam angles namely 36° or 60°. Casing in ALU black or white (AkzoNobel coating) met highly efficient thin cooling fin structure for fast cooling of the CITIZEN COB. Due to its flexible adjustment (360°/90°), it can be used for both ceiling and wall mounting. The module: Black - 25W - 2008Lm - IP20 - 2700K - lens 36 ° - L80 >40.000h - CRI >90 -Including FlickrFree dimmable driver - 3 years warranty. Optionally provided with honeycomb (avoid direct view) and/or golden inner ring (replaceable)


































Voltron® Lighting Group

Technical product sheet

Technical data

Productnumber	Barcode	ССТ	IP value	Led chip
ELEG-25W-2700K- BL-BL-36	LH-1537	2700	20	CITIZEN COB
Number of LED	Wattage	Height	Diameter	Finish color
1	25W	25CM	6CM	Black
CRI Ra	Lxx @Ta=25°C	UGR	MacAdam	Lumen
>90	L80>40.000	<19	3	2008Lm
Spread angle	Tiltable	Dimmable	Driver included	Constant current
36°	90°	V	V	V
Packed per				

Specification text*

1


Professional TRACK LED fixture for mounting on 3-phase Nordic Global Pro rail or similar. Black lacquered ALU housing (AkzoNobel brand) high efficient thin cooling fin structure for accelerated cooling of the LEDs. The light sources are replaceable. For every light source there is a lens that is also replaceable. Luminaire is always including driver. The driver is flicker-free, which increases lighting comfort. Inner ring can be replaced with a gold color as an option. An optional honeycomb filter can be installed for a softer light emission. Light is 360 ° horizontally adjustable (comes with a measuring ring with indications) and 90 ° vertically adjustable (each click is 15 °) with the unique click system. Lichtbron is a COB with a light output of 2008lm at 25W. Light color 2700K. IP20 class. Extremely suitable for lighting stores, showrooms, offices, homes. With a CRI value> 90. Equipped with photo metric report and IES file for elaboration in DIALux.

^{*} Available on the website



Voltron® Lighting Group Technical product sheet

Photometric diagram



Areas of application

Shops / museums / offices / homes

Extra information

All information, specification texts, photos, technical drawings, connection diagrams, photometric .LDT files can be found via this clickable direct link: https://www.voltron-lighting.com/product/EN/73/1537/Elegance_track_light--ELEG-25W-2700K-BL-BL-36 or can be requested through your contact person.

Direct link website



Product barcode

















The Voltron® name and logo as well as product names are part of the Voltron® Lighting Group and are protected by national and international laws. The usage rights, reproduction rights as well as the intellectual rights are the exclusive property of the Voltron® Lighting Group.

Voltron® pays a lot of attention to the correctness and completeness of the information. However, it cannot be held responsible for any inaccuracy and / or omission. All images and texts are protected under copywrite law and may not be used or multiplied without express permission.